

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

1 Identification

- **Product identifier**
- **Trade name:** Ce-508 - Ce-532 Light Cement
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** Contact manufacturer/supplier
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
BlackJack Tire Supplies, Inc.
3260 N 7th St Trafficway
Kansas City, KS 66115 USA
Phone: (816) 872-1158
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2B H320 Causes eye irritation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure.
Route of exposure: Inhalation.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS02 GHS07 GHS08

Signal word: Danger

Hazard statements:

- H225 Highly flammable liquid and vapor.
- H315+H320 Causes skin and eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 1)

· **Precautionary statements:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P260	Do not breathe vapors.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

110-54-3	n-hexane	 Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336  Eye Irrit. 2B, H320	70-80%
142-82-5	heptane	 Flam. Liq. 2, H225  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	15-25%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- **Most important symptoms and effects, both acute and delayed:**

Dizziness

Coughing

May cause drowsiness or dizziness.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Cyanosis

Irritant to skin and mucous membranes.

Causes eye irritation.

Disorientation

- **Danger:**

Vapors have narcotic effect.

Suspected of damaging fertility or the unborn child.

May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Indication of any immediate medical attention and special treatment needed:**

If necessary oxygen respiration treatment.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Foam

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

Water fog / haze

- **For safety reasons unsuitable extinguishing agents:**

Water stream.

Water spray

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 3)

- **Special hazards arising from the substance or mixture**
Highly flammable liquid and vapor.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:**
Eliminate all ignition sources if safe to do so.
Cool endangered containers with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation.
Keep away from ignition sources.
Protect from heat.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
Highly flammable liquid and vapor.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Flammable gas-air mixtures may be formed in empty containers/receptacles.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide ventilation for receptacles.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 4)

- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
- **Further information about storage conditions:** Keep containers tightly sealed.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

110-54-3 n-hexane

PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m ³ , 50 ppm
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE

142-82-5 heptane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m ³ , 500 ppm Long-term value: 1635 mg/m ³ , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

· Ingredients with biological limit values:

110-54-3 n-hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis
-----------	---

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 5)

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Engineering controls:** Provide adequate ventilation.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Protection may be required for spills.
- **Limitation and supervision of exposure into the environment**
No relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form: Liquid

Color: Blue

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

· Melting point/Melting range: Not determined.

· Boiling point/Boiling range: 60-66 °C (140-151 °F)

· Flash point: -20 °C (-4 °F)

· Flammability (solid, gaseous): Not applicable.

· Auto-ignition temperature: >220 °C (>428 °F) (Estimate)

· Decomposition temperature: Not determined.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits

Lower: 1.1 Vol %

Upper: 10.3 Vol %

· Oxidizing properties: Not determined.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 6)

- | | |
|---|---|
| · Vapor pressure at 20 °C (68 °F): | 20-30 kPa |
| · Density: | |
| Relative density at 15 °C (59 °F): | 0.66-0.68 g/cm ³ (5.508-5.675 lbs/gal) |
| Vapor density: | Not determined. |
| Evaporation rate: | Not determined. |
| · Solubility in / Miscibility with Water: | Partly miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity | |
| Dynamic: | 5000 mPas |
| Kinematic at 40 °C (104 °F): | >20.5 mm ² /s |
| VOC content: | 90-95 % Vol |
| · Other information | No relevant information available. |

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Reacts violently with oxidizing agents.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**

Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
- | |
|---|
| · LD/LC50 values that are relevant for classification: |
| 142-82-5 heptane |
| Oral LD50 > 5000 mg/kg (rat) (Estimate) |

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 7)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** Based on available data, the classification criteria are not met.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.
Inhalation.
Eye contact.
Skin contact.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Repr. 2

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:**
May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure:
Inhalation.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Toxic for aquatic organisms
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 8)

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, ADR, IMDG, IATA** UN1133

- **UN proper shipping name**

- **DOT** Adhesives
- **ADR** ADHESIVES, ENVIRONMENTALLY HAZARDOUS
- **IMDG** ADHESIVES, MARINE POLLUTANT
- **IATA** ADHESIVES

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3

- **ADR**



- **Class** 3 (F1) Flammable liquids
- **Label** 3

- **IMDG**



- **Class** 3 Flammable liquids

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 9)

· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards	Product contains environmentally hazardous substances: heptane, n-hexane
· Marine pollutant:	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· ADR	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· IMDG	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· IATA	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 10)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3 | n-hexane

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

110-54-3 | n-hexane

II

142-82-5 | heptane

D

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** March 17, 2017 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: March 17, 2017

Revision: March 17, 2017

Trade name: Ce-508 - Ce-532 Light Cement

(Cont'd. of page 11)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com